

EV-LPD3

1.0M Low Power Video Doorbell

Features:

- 720P resolution,clear and fine images;
- PIR infrared sensor about the human body, Passive induction;
- 24V alternating current charging module and pressure induction module
- Advanced H.264 video compression,Super low rate,high definition quality of image;
- Professional anti-lightning,conform to GB/T17626.5 and IEC61000-4-5。
- Support various mobile monitoring(iPhone,Android);
- Support cloud technology,easy to achieve network penetration, fro in-line and alarm information pushed



Parameters:

Model	EV-LPD3
System structure	Embedded RTOS,dual-core 32bit DSP(Hi3518EV201),pure hard compression ,watch dog
Sensor	1.0M 1/4" SC2145H CMOS sensor ,color 0.1Lux@F1.2,black/white 0.01Lux@F1.2
Video compression	H.264+/H.264,support dual stream,AVI;0.1M~6Mbps variable;1~30f/s variable
Image output	Main stream: 1280*720@25fps; sub-stream: 704*576@25fps;
Shutter	1/50(1/60)s to 1/10,000s
Lens	Ultra wide angle of view
Day and night	Support IR-CUT
Noise reduction	Support 2D/3D
Wide dynamic	Support digital
Auto iris	N/A
Audio compression	G.711,support two-way audio&talk, audio&video synchronization
Audio interface	1ch input,level:2Vp-p,impedance:1kΩ,support sound pick-up input;1ch output,impedance:16Ω,30mw,support microphone
Network interface	N/A
Extension interface	N/A
Signal interface	One photo resistance interface,one IR-CUT interface ,support photo resistance signal and IR-CUT links to IR
Human induction	PIR infrared sensor about the human body, Passive induction
Motor interface	N/A
Alarm I/O	N/A
WIFI interface	Supports Wi-Fi, a key WPS function
Reset interface	Support a key reset function
SD Card	Supports
Reliability	Comprehensive lightning protection, 7 * 24 hours 65 °C high temperature stable and reliable testing
Intelligence analysis	N/A
Other function	Support WEB,OSD,live video transmission,motion detect and IO alarm,front-end storage/playback/download, and center reminder and image linkage,support JPEG capture; united remote client monitoring software、MYEYE;perfect SDK;
ONVIF	N/A
Mobile monitoring	Support multiple mobile monitoring (iOS、Android)
Power	Three kinds of power supply option:1-DC5V 2-AC24V/0.5A 3-2*18650 Rechargeable Battery
Dimension	145mm*75mm*35mm
Other	N/A